

K4ECUP05VV

ELECTRIC RANGE 2 PLATES + OPEN CABINET



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Height-adjustable stainless steel legs.

Accessories available **on demand**.

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://ata.nt-rt.ru/> || aat@nt-rt.ru



TECHNICAL SPECIFICATIONS

Width: 400 mm

Depth: 900 mm

Height: 850 mm

Weight: 48 kg

Volume: 0.56 m³

Electrical power: 8.00 kW



K4ECUP10FF

ELECTRIC RANGE 4 PLATES + ELECTRIC OVEN 2/1 GN



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges. Double-skinned moulded oven door and AISI 304 elliptical cross-section designed handle.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Electric static oven 2/1 GN suitable for 2/1 GN trays. Stainless steel AISI 430 oven cooking chamber and thick stainless steel oven floor. Stainless steel removable oven grill.

Insulation of the cooking chamber and of the oven door ensured by a layer of high temperature resistant ceramic fibre.

Heating obtained through **heating elements placed under the bottom and on the top of the cooking chamber**. Equipped with a thermostat that adjusts the temperature between 90°C and 300°C. Possibility to select different types of heating: from below only, from above only or both from below and above through a selector.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 800 mm

Depth: 900 mm

Height: 850 mm

Weight: 160 kg

Volume: 0.99 m³

Electrical power: 21.40 kW



K4ECUP10VV

ELECTRIC RANGE 4 PLATES + OPEN CABINET



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 800 mm

Depth: 900 mm

Height: 850 mm

Weight: 94 kg

Volume: 0.99 m³

Electrical power: 16.00 kW



K4ECUP15FF

ELECTRIC RANGE 6 PLATES + ELECTRIC OVEN 2/1 GN + OPEN CABINET



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges. Double-skinned moulded oven door and AISI 304 elliptical cross-section designed handle.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Electric static oven 2/1 GN suitable for 2/1 GN trays **and open cabinet**. Stainless steel AISI 430 oven cooking chamber and thick stainless steel oven floor. Stainless steel removable oven grill.

Insulation of the cooking chamber and of the oven door ensured by a layer of high temperature resistant ceramic fibre.

Heating obtained through **heating elements placed under the bottom and on the top of the cooking chamber**. Equipped with a thermostat that adjusts the temperature between 90°C and 300°C. Possibility to select different types of heating: from below only, from above only or both from below and above through a selector.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 1200 mm

Depth: 900 mm

Height: 850 mm

Weight: 203 kg

Volume: 1.43 m³

Electrical power: 29.40 kW



K4ECUP15VV

ELECTRIC RANGE 6 PLATES + OPEN CABINET



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Height-adjustable stainless steel legs.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 1200 mm

Depth: 900 mm

Height: 850 mm

Weight: 120 kg

Volume: 1.43 m³

Electrical power: 24.00 kW



K4ECUP05TT

TOP UNIT ELECTRIC RANGE 2 PLATES



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 400 mm

Depth: 900 mm

Height: 250 mm

Weight: 40 kg

Volume: 0.26 m³

Electrical power: 8.00 kW



K4ECUP10TT

TOP UNIT ELECTRIC RANGE 4 PLATES



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS



Width: 800 mm
Depth: 900 mm
Height: 250 mm
Weight: 74 kg
Volume: 0.47 m³
Electrical power: 16.00 kW



K4ECUP15TT

TOP UNIT ELECTRIC RANGE 6 PLATES



PRODUCT DESCRIPTION

Stainless steel frame. Athermic thermoset plastic knobs with useful screen printed edges.

Heating obtained through **cast iron square electric plates**. Heating elements fixed on the plate bottom, embedded in a layer of insulating material. Each hotplate is provided with a selector, which enables the variation of the heat output **from maximum to minimum in seven positions**. Safety ensured by a temperature limit-switch situated inside the hotplate.

AISI 304 moulded 2 mm-thick work surface presenting a reverse drawing for perfect lodging the electric plates, easy cleaning and avoiding liquid damaging electric parts. Stainless steel AISI 304 front panel.

Laser-cut work top finishing for "head-to-head" matching and binding fastening.

Accessories available **on demand**.



TECHNICAL SPECIFICATIONS

Width: 1200 mm

Depth: 900 mm

Height: 250 mm

Weight: 100 kg

Volume: 0.67 m³

Electrical power: 24.00 kW



Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://ata.nt-rt.ru/> || aat@nt-rt.ru