

AF521

FRONT-LOADING DISHWASHER - TOTAL POWER 3,5 KW



PRODUCT DESCRIPTION

BEST WASH

Stainless steel structure and tank 18/10 AISI 304. Wide double-skinned balanced door.

Stainless steel upper and lower coplanar wash and rinse arms.

Stainless steel heating elements, resistant to corrosion and limescale.

Temperature thermometer. Possibility to change the cycle parameters.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Standard equipped with built-in rinse aid dispenser for the best drying results. **Standard equipped** with built-in connection for detergent dispenser.

Standard equipped with built-in connection for drain pump. **Standard equipped** with built-in connection for WiFi module.

Wide range of options available **on demand**. **Standard equipped** with a basket for plates and a basket for cups.

Performance Line stands as the more matching the needs of those chefs looking for the best washing performance. Brilliant washing results thanks to its cycles: it is possible to optimize the washing performances according to the type of crockery.

Highly resistant and anti-scratch capacitive display, designed to bear with any modern kitchen stress.

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://ata.nt-rt.ru/> || aat@nt-rt.ru



TECHNICAL SPECIFICATIONS

Width: 600 mm

Depth: 600 mm

Height: 820 mm

Volume: 0.30 m³

Rack dimensions: 500x500 mm

Useful height: 330

Electrical power: 3.50 kW

Electric power: 230 V / 1 - 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Dishes/Hour: 1080-108



AF881

FRONT-LOADING DISHWASHER - TOTAL POWER 6,8 KW



PRODUCT DESCRIPTION

WASH EURONORMS TRAYS!

Stainless steel structure 18/10 AISI 304. Double-skinned balanced and moulded door for easily taking out the basket. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms.

Stainless steel surface filter in the tank for collecting solid waste.

Temperature thermometer. Possibility to change the cycle parameters.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Standard equipped with built-in rinse aid dispenser for the best drying results. **Standard equipped** with built-in connection for detergent dispenser.

Standard equipped with the connection for the WiFi module.

Wide range of options available **on demand**. **Standard equipped** with a basket for plates and a basket for cups.

Double water filtration system with stainless steel filters helps you in keeping water cleaner for longer. 20% less water is needed in the washing tank as compared to the model AF56 for energy and detergent savings.

Double-skinned, insulated washing tank increases your comfort thanks to lower noise and remarkable energy savings.

Extremely versatile: thanks to its wide door opening of 40 cm it can wash even Eurornorms trays.

Maximum ergonomics! The increased working height at 1.2 mt means that loading and unloading basket is easier.

Highly resistant and anti-scratch capacitive display, designed to bear with any modern kitchen stress.



TECHNICAL SPECIFICATIONS

Width: 600 mm
Depth: 600 mm
Height: 1275 mm
Rack dimensions: 500x500 mm
Useful height: 405
Electrical power: 6.80 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Dishes/Hour: 1080-108



AF521D

FRONT-LOADING DISHWASHER WITH BUILT-IN WATER SOFTENER



PRODUCT DESCRIPTION

BEST WASH

Stainless steel structure and tank 18/10 AISI 304. Wide double-skinned balanced door.

Stainless steel upper and lower coplanar wash and rinse arms.

Stainless steel heating elements, resistant to corrosion and limescale.

Temperature thermometer. Possibility to change the cycle parameters.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Standard equipped with built-in rinse aid dispenser for the best drying results. **Standard equipped** with built-in connection for detergent dispenser.

Standard equipped with built-in connection for drain pump. **Standard equipped** with built-in connection for WiFi module.

Wide range of options available **on demand**. **Standard equipped** with a basket for plates and a basket for cups.

Performance Line stands as the more matching the needs of those chefs looking for the best washing performance. Brilliant washing results thanks to its cycles: it is possible to optimize the washing performances according to the type of crockery.

Highly resistant and anti-scratch capacitive display, designed to bear with any modern kitchen stress.



TECHNICAL SPECIFICATIONS

Width: 600 mm

Depth: 600 mm

Height: 820 mm

Volume: 0.30 m³

Rack dimensions: 500x500 mm

Useful height: 330

Electrical power: 3.50 kW

Electric power: 230 V / 1 - 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Dishes/Hour: 1080-108



AF611

FULL-TOUCH FRONT-LOADING DISHWASHER - TOTAL POWER 5 KW



PRODUCT DESCRIPTION

PREMIUM FINISHING

Stainless steel structure 18/10 AISI 304. Double-skinned balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms.

Stainless steel surface filter in the tank for collecting solid waste.

Temperature thermometer. Possibility to change the cycle parameters.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Standard equipped with built-in rinse aid dispenser for the best drying results. **Standard equipped** with built-in connection for detergent dispenser.

Standard equipped with the connection for the WiFi module.

Wide range of options available **on demand**. **Standard equipped** with a basket for plates and a basket for cups.

Featuring the most refined design, well identified by their touch screen display and rounded and smooth internal shape.

Double water filtration system with stainless steel filters helps you in keeping water cleaner for longer. 20% less water is needed in the washing tank as compared to the model AF56 for energy and detergent savings.

HD Full-Touch display with colored icons, the most intuitive and easy to use.



TECHNICAL SPECIFICATIONS

Width: 600 mm

Depth: 600 mm

Height: 850 mm

Volume: 0.31 m³

Rack dimensions: 500x500 mm

Useful height: 350

Electrical power: 5.00 kW

Electric power: 230 V / 1 - 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Dishes/Hour: 1080-108



AF781

FULL-TOUCH FRONT-LOADING DISHWASHER - TOTAL POWER 6,5 KW



PRODUCT DESCRIPTION

PREMIUM FINISHING

Stainless steel structure 18/10 AISI 304. Double-skinned balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms.

Stainless steel surface filter in the tank for collecting solid waste.

Temperature thermometer. Possibility to change the cycle parameters.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Standard equipped with built-in rinse aid dispenser for the best drying results. **Standard equipped** with built-in connection for detergent dispenser.

Standard equipped with the connection for the WiFi module.

Wide range of options available **on demand**. **Standard equipped** with a basket for plates and a basket for cups.

Featuring the most refined design, well identified by their touch screen display and rounded and smooth internal shape.

Double water filtration system with stainless steel filters helps you in keeping water cleaner for longer. 20% less water is needed in the washing tank as compared to the model AF56 for energy and detergent savings.

HD Full-Touch display with colored icons, the most intuitive and easy to use. with colored icons, the most intuitive and easy to use.

Double-skinned, insulated washing tank increases your comfort thanks to lower noise and remarkable energy savings.



TECHNICAL SPECIFICATIONS

Width: 600 mm
Depth: 600 mm
Height: 850 mm
Volume: 0.31 m³
Rack dimensions: 500x500 mm
Useful height: 350
Electrical power: 6.50 kW
Electric power: 230 V / 1 - 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Dishes/Hour: 1080-108



Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://ata.nt-rt.ru/> || aat@nt-rt.ru