

ATR1500

RACK CONVEYOR DISHWASHER 1500 PLATES PER HOUR



PRODUCT DESCRIPTION

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

The built-in **W.A.G.P.** system ensures excellent rinsing and prevents dirty water from flowing back to the main water system.

Wide range of accessories and options available **on demand**: drying tunnel (**AZ 75**), splash guard (**PC 75**), rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three baskets for plates and a basket for cutlery.

IPX5 protection.

Optional on demand: connection to cold water for a total power of **30,3 kW**

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47

<https://ata.nt-rt.ru/> || aat@nt-rt.ru



TECHNICAL SPECIFICATIONS

Width: 1200 mm
Depth: 720 mm
Height: 1380 mm
Volume: 1.18 m³
Rack dimensions: 500x500 mm
Useful height: 430
Electrical power: 17.10 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Racks/Hour: 85
Dishes/Hour: 1500
WAGP: Standard



ATR1800

RACK CONVEYOR DISHWASHER 1800 PLATES/HOUR



PRODUCT DESCRIPTION

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

The built-in **W.A.G.P.** system ensures excellent rinsing and prevents dirty water from flowing back to the main water system.

Wide range of accessories and options available **on demand**: drying tunnel (**AZ 75**), splash guard (**PC 75**), rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for plates and a rack for tableware.

IPX5 protection

Option on demand: connection to cold water for a total power of **30,3 kW**.



TECHNICAL SPECIFICATIONS

Width: 1400 mm

Depth: 720 mm

Height: 1380 mm

Volume: 1.18 m³

Rack dimensions: 500x500 mm

Useful height: 430

Electrical power: 20.10 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 100

Dishes/Hour: 1800

WAGP: Standard



ATR2700ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 2700 PLATES/HOUR



PRODUCT DESCRIPTION

ATR2700 ES: Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 80 racks/hour (speed 1) or 115 racks/hour (speed 2) or 150 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Equipped with non-return valve avoiding dirty water to flow back into the main water system (DVGW approved).

Standard equipped with a stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for plates, a rack for tableware and a rack for glasses.

IPX5 protection

Option on demand: connection to cold water for a total power of **36,3 kW**.



TECHNICAL SPECIFICATIONS

Width: 1570 mm
Depth: 800 mm
Height: 1580 mm
Volume: 1.99 m³
Rack dimensions: 500x500 mm
Useful height: 410
Electrical power: 27.30 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Racks/Hour: 80-115-150
Dishes/Hour: 1440-2070-2700



ATR3200ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 3200 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR3200 ES: Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, one washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 90 racks/hour (speed 1) or 135 racks/hour (speed 2) or 180 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **36,1 kW**.



TECHNICAL SPECIFICATIONS

Width: 1870 mm

Depth: 800 mm

Height: 1580 mm

Volume: 2.36 m³

Rack dimensions: 500x500 mm

Useful height: 410

Electrical power: 27.10 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 90-135-180

Dishes/Hour: 1620-2430-3200



ATR3800ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 3800 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR3800 ES: Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, one washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 110 racks/hour (speed 1) or 160 racks/hour (speed 2) or 210 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **37,3 kW**.



TECHNICAL SPECIFICATIONS

Width: 2170 mm
Depth: 800 mm
Height: 1580 mm
Volume: 2.74 m³
Rack dimensions: 500x500 mm
Useful height: 410
Electrical power: 28.30 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Racks/Hour: 110-160-210
Dishes/Hour: 1980-2880-3780



ATR4300ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 4300 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR4300 ES: Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, one washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 140 racks/hour (speed 1) or 190 racks/hour (speed 2) or 240 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with four racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **38,5 kW**.



TECHNICAL SPECIFICATIONS

Width: 2470 mm
Depth: 800 mm
Height: 1580 mm
Volume: 3.12 m³
Rack dimensions: 500x500 mm
Useful height: 410
Electrical power: 29.50 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Racks/Hour: 140-190-240
Dishes/Hour: 2520-3420-4320



ATR4900ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 4900 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR4900 ES: Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, a double washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 160 racks/hour (speed 1) or 215 racks/hour (speed 2) or 270 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with four racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **48,5 kW**.



TECHNICAL SPECIFICATIONS

Width: 3070 mm
Depth: 800 mm
Height: 1580 mm
Volume: 3.88 m³
Rack dimensions: 500x500 mm
Useful height: 410
Electrical power: 36.50 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Racks/Hour: 160-215-270
Dishes/Hour: 2880-3870-4860



ATR5400ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 5400 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR5400 ES: Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, a double washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 190 racks/hour (speed 1) or 245 racks/hour (speed 2) or 300 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with four racks for dishes, a rack for tableware and two racks for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **49,7 kW**.



TECHNICAL SPECIFICATIONS

Width: 3370 mm

Depth: 800 mm

Height: 1580 mm

Volume: 4.26 m³

Rack dimensions: 500x500 mm

Useful height: 410

Electrical power: 40.70 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 190-245-300

Dishes/Hour: 3420-4410-5400



ATR2700ED

RACK CONVEYOR DISHWASHER RIGHT-HAND SIDE ENTRY 2700 PLATES/HOUR



PRODUCT DESCRIPTION

ATR2700 ED: Rack conveyor dishwasher with **electric feeding** and **right-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 80 racks/hour (speed 1) or 115 racks/hour (speed 2) or 150 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **36,3 kW**.



TECHNICAL SPECIFICATIONS

Width: 1570 mm

Depth: 800 mm

Height: 1580 mm

Volume: 1.99 m³

Rack dimensions: 500x500 mm

Useful height: 410

Electrical power: 27.30 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 80-115-150

Dishes/Hour: 1440-2070-2700



ATR3200ED

RACK CONVEYOR DISHWASHER RIGHT-HAND SIDE ENTRY 3200 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR3200 ED: Rack conveyor dishwasher with **electric feeding** and **right-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, one washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 90 racks/hour (speed 1) or 135 racks/hour (speed 2) or 180 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **36,1 kW**.



TECHNICAL SPECIFICATIONS

Width: 1870 mm

Depth: 800 mm

Height: 1580 mm

Volume: 2.36 m³

Rack dimensions: 500x500 mm

Useful height: 410

Electrical power: 27.10 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 90-135-180

Dishes/Hour: 1620-2430-3240



ATR3800ED

RACK CONVEYOR DISHWASHER RIGHT-HAND SIDE ENTRY 3800 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR3800 ED: Rack conveyor dishwasher with **electric feeding** and **right-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, one washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 110 racks/hour (speed 1) or 160 racks/hour (speed 2) or 210 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **37,3 kW**.



TECHNICAL SPECIFICATIONS

Width: 2170 mm

Depth: 800 mm

Height: 1580 mm

Volume: 2.74 m³

Rack dimensions: 500x500 mm

Useful height: 410

Electrical power: 28.30 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 110-160-210

Dishes/Hour: 1980-2880-3780



ATR4300ED

RACK CONVEYOR DISHWASHER RIGHT-HAND SIDE ENTRY 4300 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR4300 ED: Rack conveyor dishwasher with **electric feeding** and **right-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, one washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 140 racks/hour (speed 1) or 190 racks/hour (speed 2) or 240 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with four racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **38,5 kW**.



TECHNICAL SPECIFICATIONS

Width: 2470 mm

Depth: 800 mm

Height: 1580 mm

Volume: 3.12 m³

Rack dimensions: 500x500 mm

Useful height: 410

Electrical power: 29.50 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 140-190-240

Dishes/Hour: 2520-3420-4320



ATR4900ED

RACK CONVEYOR DISHWASHER RIGHT-HAND SIDE ENTRY 4900 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR4900 ED: Rack conveyor dishwasher with **electric feeding** and **right-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, a double washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 160 racks/hour (speed 1) or 215 racks/hour (speed 2) or 270 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with four racks for dishes, a rack for tableware and a rack for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **48,5 kW**.



TECHNICAL SPECIFICATIONS



Width: 3070 mm

Depth: 800 mm

Height: 1580 mm

Volume: 3.88 m³

Rack dimensions: 500x500 mm

Useful height: 410

Electrical power: 36.50 kW

Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz

Racks/Hour: 160-215-270

Dishes/Hour: 2880-3870-4860



ATR5400ED

RACK CONVEYOR DISHWASHER RIGHT-HAND SIDE ENTRY 5400 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR5400 ED: Rack conveyor dishwasher with **electric feeding** and **right-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

One pre-washing area, a double washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 190 racks/hour (speed 1) or 245 racks/hour (speed 2) or 300 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Standard equipped with non-return valve avoiding dirty water flowing back into the main water system (DVGW approved).

Standard equipped with stainless steel connection for detergent dispenser in each wash tank. **Standard equipped** with built-in connection for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with four racks for dishes, a rack for tableware and two racks for glasses.

IPX5 protection.

Option on demand: connection to cold water for a total power of **49,7 kW**.



TECHNICAL SPECIFICATIONS

Width: 3370 mm
Depth: 800 mm
Height: 1580 mm
Volume: 4.26 m³
Rack dimensions: 500x500 mm
Useful height: 410
Electrical power: 37.70 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Racks/Hour: 190-245-300
Dishes/Hour: 3420-4410-5400



Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(7172)727-132

Киргизия +996(312)96-26-47